


- Zet rastereffecten Illustrator op 300dpi.
- Converteer alle tekst naar paden.
- Maak juiste wit-separatie bij de uitvoering: Metallic, Transparant of Kraftpapier.
- Design wordt gerepeteerd op de drukvorm. Zorg voor doorlopend beeld aan de snijranden i.v.m. snijtolerantie van 2mm.

Seal. Vermijd hier plaatsing van tekst en pictogrammen

 Seal area. Avoid placing text and icons here


Snijlijn (optioneel ronde hoeken)

 Cutting (optional rounded corners)

Overvul zone

 Bleed zone

Oogblok (t.b.v. snijproces)
Te behouden in finale layout!


 Eye mark (for post print cutting)
To keep in final design!

Optioneel Eurohole
Min. 5 mm / Max 40 mm
vanaf de boven- én onderzijde



Optional Eurohole
Min. 5 mm / Max 40 mm
from the top- and bottomside

Optioneel Ventiel
Min. 20 mm / Max 120 mm
vanaf de boven- of onderzijde



Optional Valve
Min. 20 mm / Max 120 mm
from the top- or bottomside

- Put Illustrator Document Raster Effect to 300dpi.
- Convert all text to paths.
- Create correct white separation when opting for Transparent, Metallic or Kraft paper execution.
- Design is repeated on print form. Therefore take care of continuous image on cutting edges as cutting tolerance is 2 mm.